

Digital Thermometers



LifeSource digital thermometers provide accurate temperature readings at the touch of a button.

LifeSource digital thermometers provide a safe, convenient alternative to traditional glass mercury thermometers. A&D Medical offers three digital thermometers to meet different needs. Each thermometer is encased in durable plastic and are safe for all ages. A&D Medical's LifeSource thermometers provide readings in either 10 or 60 seconds.

The DT-607 Digital Thermometer provides 60 second measurements at an economical price point. The DT-609 Thermometer provides 10 second measurements with an extra large display and the DT-611 Thermometer provides 10 second measurements with a soft, flexible tip.

These thermometers have features that include a digital temperature readout, last measurement memory, audible beep when a measurement is complete and automatic shut off.

- Includes protective carrying case for safe storage
- Bilingual instruction guide

For questions about LifeSource products, call us toll-free at 1-800-461-0991 and a specially trained representative will assist you.

- Accurate readings in Celsius and Fahrenheit
- Mercury free
- Beeps when peak temperature reached
- Automatic shut-off
- Automatic last reading memory

LifeSource Digital Thermometers

DT-607 Digital Thermometer

- 60 second measurement time
- Reads Celsius and Fahrenheit
- Oral, underarm or rectal use
- Water-resistant
- Last temperature reading
- Automatic shut-off
- Mercury free
- Carrying case included
- UPC: 6-22006-78112-9



DT-609 Fast-Read Thermometer

- 10 second measurement time
- Reads Celsius and Fahrenheit
- Oral, underarm or rectal use
- Water-resistant
- Last temperature reading
- Automatic shut-off
- Mercury free
- Carrying case included
- UPC: 6-22006-78111-2



DT-611 Flex-Tip Thermometer

- 10 second measurement time
- Reads Celsius and Fahrenheit
- Oral, underarm or rectal use
- Water-resistant
- Last temperature reading
- Automatic shut-off
- Mercury free
- Carrying case included
- UPC: 6-22006-78110-5



Technical Specifications

Range	90.0° - 110.0° F (32.0° - 44.0° C)
Accuracy	± 0.2°F between 96.0° and 104.2° F; ± 0.1°C between 34.0° and 42.0° C. At standard room temperature of 64° - 82.4° F (18.0° - 28° C)
Display	0.01° F (0.01° C)
Battery	One 1.55V button size battery (LR41 or equivalent)
Power Consumption	Less than or equal to 0.09 mW
Battery Life	Approximately 3000 measurements
Weight	Approximately 13 grams including battery
Fast Read	DT-703: Provides readings in approximately 60 seconds DT-704: Provides readings in approximately 10 seconds DT-705: Provides readings in approximately 10 seconds
Beeper	Beeps after peak temperature is reached.

Packaging and Shipping Specifications

Selling Unit	D x W x H (cm)	WT (kg.)
DT-607	1.50 x 8.00 x 17.50	0.033
DT-609	2.50 x 8.00 x 17.50	0.048
DT-611	2.50 x 8.00 x 17.50	0.051
Unit Case (12 units)	D x W x H (cm)	WT (kg.)
DT-607	18.01 x 8.79 x 15.19	0.07
DT-609	18.01 x 8.79 x 26.01	0.11
DT-611	18.01 x 8.79 x 26.01	0.11



Ask your Auto Control Medical Representative about other LifeSource products.

- Blood Pressure Monitors
- Digital Thermometers
- Personal Scales
- Stethoscopes

For questions about LifeSource, call us toll-free at 1-800-461-0991 or visit our website at www.autocontrol.com

Distributed by:



Montreal • Toronto
1-800-461-0991
www.autocontrol.com



1555 McCandless Drive
Milpitas, CA 95035
www.LifeSourceOnline.com

